

# FS40 Fixed Industrial Scanner

Comprehensive feature set, extraordinary flexibility, unsurpassed value

Today more than ever, the increasing demands of international commerce and its global supply chain are pressuring companies to deliver more — and to do it faster. From manufacturing to logistics to the end customer, success is driven by the ability to quickly move and track the products that drive your business.



Address it all with Zebra's FS40 Fixed Industrial Scanner,<sup>1</sup> designed to meet the comprehensive requirements of today's production and delivery processes. The FS40 easily keeps pace with the fastest moving operations, enabling track-and-trace through the automatic and flawless decode of information on every part and package as it moves through production, storage and fulfillment — capturing even the most challenging barcodes. The result? Best-in-class production, warehousing, distribution and logistics processes that inspire businesses to reach their highest potential.



Zebra's FS40 Fixed Industrial Scanner sets the bar for simplicity, advanced data capture and return on investment. It all starts with Zebra Aurora™ — a powerful and intuitive software platform that makes it exceptionally easy to set up, deploy and run all Zebra Fixed Industrial Scanners, including the FS40. Once up and running, Zebra-exclusive features like ImagePerfect+ and PRZM Intelligent Imaging deliver first-time, every-time data capture. As your needs change, easily add support for new codes, increase scanning speed and upgrade to machine vision functionality — all through the simple purchase of software licenses that future-proof your investment. Take your success to the next level with extraordinary visibility into the processes that power your operations with the FS40 — only from Zebra.

## Zebra Aurora™ Software

### A single unified platform across Zebra's fixed industrial scanner and machine vision portfolio

Zebra Aurora brings a new level of elegance and simplicity to controlling enterprise-wide manufacturing and logistics automation solutions. This powerful interface makes it easy to set up, deploy and run all of Zebra's Fixed Industrial Scanners and Machine Vision Smart Cameras, while eliminating the need for different tools.

### For experts and beginners

Experienced and first-time users can easily navigate the highly intuitive modern interface, reducing training and deployment time. Experienced users will appreciate easy access to all functions and streamlined processes, while first-time users are guided through all the steps in the proper order. And if users need a little help, Learn-As-You-Go offers built-in tutorials, walk-throughs and videos on all aspects of the software and its comprehensive management toolset.

The FS40 — Enable performance. Inspire potential. Experience the difference with Zebra.

For more information, visit [www.zebra.com/fs40](http://www.zebra.com/fs40)

## Easy to set up

### Automatic setup with Auto-Tune

Just Auto-Tune and run for consistent, reliable read rates – right out of the box. With the press of one button, Auto-Tune dials in the perfect image for faster and more accurate set up.

### IoT ready with Zebra Savanna™

The IoT-ready FS40 can send images to Zebra's subscription-based cloud service, Zebra Savanna™ — or any other cloud service — allowing you to meet industry regulations or store images for further analysis, all without the need to purchase and manage servers.

### Power it all over Ethernet

Reduce setup complexity and cost with support for Power-over-Ethernet (PoE). This standard feature powers the FS40 and attached accessories right over the network, eliminating the cost of power drops and power supplies. Don't have a PoE infrastructure? No problem. You can also power the FS40 with a standard 24V DC power supply or even a standard USB-C port.

### Limitless expansion options with USB-C

Ready for a new level of flexibility? USB-C allows you to power your camera with a single cable and provides limitless accessory options. Seamlessly integrate with other Zebra devices such as a printer or tablet. You can also backup your system or save images for future analysis by connecting external storage devices to the FS40.

## Easy to deploy

### Programmable input/output (I/O) ports

Get the ultimate in I/O flexibility. Up to nine digital I/O ports can be individually controlled to expand application functionality and improve error-proofing. Support additional peripherals, activate lights, or trigger an action to more fully automate your processes.

### Powerful integrated lighting

Reliable barcode capture starts with the highest quality image — something which frequently requires the purchase and management of expensive, external lighting. With Zebra's FS40, you can do more with less via the powerful integrated illumination system. Choose the lighting that's best suited for the types of codes you scan today — red, white, blue, infrared, or a single model that includes them all. The result? High quality images for highly reliable barcode reading.

### Ultra-rugged and ready for industrial spaces

Rely on dependable operation in the most demanding environments with an ultra-rugged design. The aluminum housing is chemical and oil resistant. IP65 and IP67 sealing ratings make the device dust tight and able to withstand high-power wash downs — or even total immersion in water.

### Operator feedback/status indicators

With 360° LED lights, your operators can instantly see decode status. Workers can see at a glance if a decode was successful or unsuccessful — protecting product quality and traceability. Five built-in camera status LEDs — Power, Online/Run, Focus Warning, Error and Ethernet Status — make it easy to verify whether cameras are fully operational or in need of attention. In addition, a beeper with adjustable volume provides an audible cue of a successful decode, so workers can keep their eyes on the job — instead of the device.

### Aiming simplicity

A unique 8-point sunburst pattern with sharp, laser-generated lines makes it easy to ensure that barcodes are in the field of view for foolproof, reliable aiming — and faster deployment.

### Added flexibility with Zebra

#### Aurora HMI dashboard

Give workers actionable intelligence right where they need it — at their station. Operators can see and interact with the Zebra Aurora Human Machine Interface (HMI) dashboard via any web browser or by directly connecting a monitor to the FS40. The need to install a PC at every workstation is eliminated, reducing hardware requirements and installation costs.

#### Simple, easy and fast integration with your network infrastructure

Built-in Ethernet/IP with Add-On Profile, PROFINET and other network protocols enable painless integration with any common PLC or host system. Network architecture is simplified and deployment time and cost are reduced.

## Easy to run

### First-time every-time data capture

Superior optics and Zebra's exclusive PRZM Intelligent Imaging technology work together to deliver the reliable data capture you need to keep your operations running at peak capacity. The optical system enables the simultaneous capture of multiple barcodes, extends read ranges and focal distances,

## Key Differentiators

The FS40 is loaded with class-leading features, including:

### ImagePerfect+

#### Achieve the highest read rates with perfect images

Capture up to 16 different images of a single item, each with its own unique setting for focus, exposure, gain, illumination control and more.

### PRZM Intelligent Imaging

#### First-time every-time barcode capture

Capture virtually any barcode in practically any condition — from 1D and 2D barcodes on a fast-moving conveyor belt, to DPM codes that are printed on challenging curved and reflective surfaces and more.

### Software Licensing

#### Add what you need, whenever you need it

Add support for new barcode symbologies, faster barcode capture and all the machine vision tools you need through simple software licensing.

### USB-C

#### Limitless expansion options

Easily connect all the peripherals you need — from a printer or tablet to an external drive and more.

### PoE+

#### Power it all over Ethernet

Power the FS40 right over your Ethernet cable — no more costly power drops and no more power supplies to purchase and manage.

## PRODUCT SPEC SHEET

### FS40 FIXED INDUSTRIAL SCANNER

and allows a larger field of view to capture more information with less equipment. PRZM Intelligent Imaging is designed for the data capture demands of your environment, enabling the first-time capture of virtually any barcode in practically any condition — from damaged or poorly printed 1D and 2D barcodes on a fast-moving conveyor belt to challenging under- or over-marked DPM codes printed on curved and reflective surfaces.

#### **Achieve the highest read rates with ImagePerfect+**

Uneven lighting and the need to read barcodes at various distances can create the need for additional cameras, external lights or complex costly custom code — additions that can substantially increase overall costs as well as the total cost of ownership. Address it all with a groundbreaking new feature — ImagePerfect+. This Zebra-exclusive feature captures up to 16 different images of a single item, each with its own unique setting for focus, exposure, gain, illumination control and more. The result? High quality images that enable high read rates. A significant reduction in solution complexity. And a lower total cost of ownership.

#### **Capture all the data that drives your business**

Do it all with the FS40 — 1D, 2D and DPM barcodes, plus OCR human readable characters. Choose the configuration that supports the codes that drive your business processes today, knowing you can add functionality to meet the data capture needs of tomorrow. Just purchase licenses to support additional barcode symbologies, increased scanning speed, or upgrade to an MV Toolset to turn your FS40 into a Smart Camera, complete with machine vision capabilities.

#### **Rapid troubleshooting with**

##### **Golden Image Compare**

If any barcode reads fail, this Zebra-only tool allows you to quickly identify and resolve the issue by comparing any image to a golden 'perfect' image created at setup. The source of any image

degradation can be immediately diagnosed, enabling the rapid correction needed to minimize downtime — from a dirty lens or a lighting problem to misalignment of the camera, which can skew the image and impact dimensional accuracy.

#### **Identify and correct setting changes with Job Compare**

This unique tool compares current settings in the job and the camera to all initial settings, allowing users to revert back to the original settings with one click.

#### **Scan all barcodes simultaneously with ManyCode**

Need to read multiple barcodes on an item? With one click in Zebra Aurora, you can enable ManyCode mode to capture all barcodes simultaneously, regardless of quantity, symbology or barcode data.

#### **Eliminate production delays with Dual Ethernet connections**

The FS40 is the only Fixed Industrial Scanner in its class to offer dual Ethernet ports. Completely isolate the Controls Network to protect key production data and utilize a second Ethernet connection to send images to the cloud or local server for storage. Don't need a second Ethernet port? Just choose the single port configuration to pay only for what you need.

#### **Complete support service — everything's covered**

Get the constant peak performance and device uptime today's businesses demand with Zebra OneCare™ Essential and Select Support Services. Unexpected disruptions and unbudgeted repair expenses are eliminated. Everything is covered — including normal wear and tear and accidental damage. You can customize your support plan with numerous options to get the service level your business needs, including next-day delivery of a replacement device, on-site support, cloud-based visibility into your contracts, repair data, tech support cases — and more.

## Introducing the Fixed Industrial Scanner and Machine Vision Portfolio



FS10



FS20/VS20



FS40/VS40



FS70/VS70

# Specifications

Physical Characteristics	
<b>Dimensions</b>	2.1 in. H x 2.5 in. W x 3.6 in. D 54.0 mm H x 64.0 mm W x 91.4 mm D
<b>Weight</b>	14.1 oz./400.0 g
<b>Power</b>	10 to 30 VDC external power supply, 36W max at 24V <ul style="list-style-type: none"> <li>• Class 4 PoE+ source, 25.5W max</li> <li>• Class 3 PoE source, 13W max</li> <li>• USB Type-C host, 7.5W max at 5V, 1.5A or 15W max at 5V, 3.0A</li> </ul>
<b>Configurable IO</b>	(4) Four opto-isolated GPIO: GPIO0,1,2,3 (5) Five non-isolated GPIO: GPIO4,5,6*,7*,8* *Unavailable when External Light Mode is enabled
<b>Color and Material</b>	Industrial green aluminum housing
<b>Interface Ports</b>	(1) M12 X-Coded 1000/100/10 Mbps Ethernet (1) M12 12-pin Power/GPIO (1) M12 5-pin External Light Power & Control/GPIO (1) USB 3.0 SuperSpeed Type-C with DisplayPort Alt Mode Available with one or two Ethernet ports
<b>Communication Protocols</b>	Ethernet/IP, PROFINET, CC-Link, Modbus TCP, TCP/IP
<b>Keyboard Support</b>	Supports over 90 international keyboards
<b>User Indicators</b>	360 Degree Decode/Job Status LEDs, Power LED, Online/Run LED, Focus Warning LED, Error LED, Ethernet Status LED; Beeper (adjustable volume)
Performance Characteristics	
<b>Image Sensor</b>	Monochrome: 2.3 MP (1920 x 1200 pixels) CMOS Sensor with Global Shutter and 3.0 um Pixel Size
<b>Acquisition Rate</b>	Up to 60 frames/second
<b>Aimer</b>	Red Class II Laser; 8-point sunburst pattern
<b>Illumination</b>	Field replaceable modules: <ul style="list-style-type: none"> <li>• (8) 660nm Red LEDs</li> <li>• (8) 470nm Blue LEDs</li> <li>• (8) 850nm IR LEDs</li> <li>• (8) 2700K (Color Temperature) White LEDs</li> <li>• (4) 660nm Red LEDs + (8) 850nm IR LEDs + (4) 470nm Blue LEDs + (8) 2700K (Color Temperature) White LEDs</li> </ul>
<b>Imager Field of View</b>	SR (Standard Range): 10.8mm Liquid Lens (30° H x 19° V Nominal) WA (Wide Angle): 6.8mm Liquid Lens (46° H x 29° V Nominal)
User Environment	
<b>Operating Temp.</b>	32° F to 113° F/0° C to 45° C (10-30VDC external power supply, duty cycle-dependent) 32° F to 113° F/0° C to 40° C (POE, duty cycle-dependent)
<b>Storage Temp.</b>	-40° F to 158° F/-40° C to 70° C
<b>Environmental Sealing</b>	IP65 and IP67
<b>Humidity</b>	5% to 90% RH, non-condensing

User Environment (continued)	
<b>Shock Resistance</b>	EN 60068-2-27, 30 g; 11 ms; 3 shocks on each axis
<b>Vibration Resistance</b>	EN 60068-2-6, 14 mm @ 2 to 10 Hz, 1.5 mm @ 13 to 55 Hz; 2 g @ 70 to 500 Hz; 2 hours on each axis
Supported Symbologies <sup>2</sup>	
<b>1D</b>	Base 32 (Italian Pharma), Codabar/NW7, Code 11, Code 39, Code 93, Code 128, GS1 DataBar, I 2 of 5, Korean 3 of 5, MSI Plessey, UPC/EAN, DPM
<b>2D</b>	Aztec, Composite Codes, DataMatrix, Dotted DataMatrix, Dotcode, Han Xin, MaxiCode, PDF417, Micro PDF417, Postal Codes, QR Code, Micro QR, TLC-39, DPM
<b>OCR</b>	OCR-A, OCR-B, MICR, US Currency, Trainable OCR (available on select models or via an add-on OCR license)
Software	
<b>Management</b>	Zebra Aurora™
<b>Decoder Packages</b>	1D/2D Standard (5 FPS); 1D/2D Fast and OCR (60 FPS); 1D/2D DPM Lite and OCR (5 FPS); 1D/2D DPM Full and OCR (60 FPS); Trainable OCR (standalone license) (Decoder packages vary by SKU; software Decoder Package upgrades available via an upgrade license.)
<b>Machine Vision (MV) Toolsets</b>	Sensor, Standard, Advanced (Available via an upgrade license)
Regulatory	
<b>Environmental</b>	EN 50581:2012; EN IEC 63000:2018
<b>Electrical Safety</b>	IEC 62368-1 (Ed.2); EN 62368-1:2014/A11:2017
<b>LED Safety</b>	IEC 62471:2006 (Ed.1); EN 62471:2008
<b>EMI/EMS</b>	EN 55032:2015/A11:2020 (Class B) EN 55035:2017 EN 61000-3-2:2014 (Class A) EN 61000-3-3:2013 47 CFR Part 15, Subpart B, Class B ICES-003, Issue 7, Class B
<b>EU Declaration of Conformity</b>	2014/30/EU; 2014/35/EU; 2011/65/EU. For more information visit: <a href="http://www.zebra.com/doc">www.zebra.com/doc</a>
Accessories	
Internal illumination, external illumination, internal filters, brackets, cables, power supplies	
Warranty	
Subject to the terms of Zebra's hardware warranty statement, the FS40 is warranted against defects in workmanship and materials for a period of Two (2) Years from the date of shipment. Complete Zebra hardware product warranty statement: <a href="http://www.zebra.com/warranty">www.zebra.com/warranty</a>	
Recommended Services	
Zebra OneCare Select; Zebra OneCare Essential	

continued on page 5

## Specifications (continued)

### Decode Ranges (Typical Working Ranges)<sup>3</sup>

#### FS40-SR — 30° FOV Lens

Symbology/Resolution	Near	Far
5 mil Code 128	3 in./8 cm	22 in./56 cm
10 mil Code 128	3 in./8 cm	44 in./112 cm
15 mil Code 128	3 in./8 cm	70 in./178 cm
20 mil Code 128	3 in./8 cm	90 in./229 cm
5 mil DataMatrix	3 in./8 cm	13 in./33 cm
10 mil DataMatrix	3 in./8 cm	26 in./66 cm
15 mil DataMatrix	3 in./8 cm	39 in./99 cm
30 mil DataMatrix	3 in./8 cm	69 in./175 cm

#### FS40-WA — 46° FOV Lens

Symbology/Resolution	Near	Far
5 mil Code 128	3 in./8 cm	13 in./33 cm
10 mil Code 128	3 in./8 cm	26 in./66 cm
15 mil Code 128	3 in./8 cm	40 in./102 cm
20 mil Code 128	3 in./8 cm	54 in./137 cm
5 mil DataMatrix	3 in./8 cm	8 in./20 cm
10 mil DataMatrix	3 in./8 cm	17 in./43 cm
15 mil DataMatrix	3 in./8 cm	26 in./66 cm
30 mil DataMatrix	3 in./8 cm	50 in./127 cm

#### Footnotes

1. Some features available in a future release. Contact your Zebra Partner or sales representative for more information.
2. Refer to Product Reference Guide for complete list of symbologies.
3. Printing resolution, contrast, and ambient light dependent.

Specifications subject to change without notice.



**PEAK**  
TECHNOLOGIES

888-492-6346

[www.peaktech.com](http://www.peaktech.com)

[info@peaktech.com](mailto:info@peaktech.com)



**NA and Corporate Headquarters**  
+1 800 423 0442  
[inquiry4@zebra.com](mailto:inquiry4@zebra.com)

**Asia-Pacific Headquarters**  
+65 6858 0722  
[contact.apac@zebra.com](mailto:contact.apac@zebra.com)

**EMEA Headquarters**  
[zebra.com/locations](http://zebra.com/locations)  
[contact.emea@zebra.com](mailto:contact.emea@zebra.com)

**Latin America Headquarters**  
+1 847 955 2283  
[la.contactme@zebra.com](mailto:la.contactme@zebra.com)